

# Low Maintenance & Easy Installation

Bellaforté Slate polymer roofing tiles make installation easy—saving materials and cutting down on installation costs. With little to no upkeep and backed by DaVinci's lifetime warranty, DaVinci Slate tiles are the perfect fit for your home for generations to come.

## A Safer & More Secure Roof

Bellaforté Slate has achieved the highest possible test ratings for fire, wind and impact giving you a more secure home for your family and has been approved and preferred by cities and subdivisions nationwide.

BELLAFORTÉ SLATE SPECIFICATION CHART					
Shingle Dimensions					
Widths	12"	Thickness at Butt	1/2"		
Length	15 1/2"	Thickness at Tip	3/8"		
HIP • RIDGE • STARTER					
	One-Piece Hip & Ridge	Rake	12" Starter	Transition Piece	
Pieces / Bundle	10	20	20	10	
Lineal Ft / Bundle	10	20	20	10	
Pieces / Lineal Ft	1	1	1	1	
* At recommended 7" exposure					
FIELD SHINGLES PER ROOFING SQUARE					
Coursing	Roof Pitch	Max. Exposure	Bundles / Square	Shingles / Square	Weight / Square
Straight	4" in 12" or greater	12"	10	100	158 lbs
PACKING AND SHIPPING INFORMATION					
	# Shingles			Weight	
Per Bundle*	10			16 lbs	
Per Pallet**	720			1,152 lbs	
Per Truckload***	17,280			27,648 lbs	
* All weights are approximate ** 72 bundles per pallet *** 24 pallets per truckload					
TESTING SUMMARY					
Type of Test	Standard			Results	
Fire Test	ASTM E 108			Class A	
Impact Test	UL 2218			Class 4	
Wind Test	ASTM D 3161			Certified to 110MPH*	
Building Code Approvals: ICC-ES ESR 2119, Miami-Dade County, FL NOA No. 12-0831.01 and TDI					

\* Go to [www.davinciroofscapes.com](http://www.davinciroofscapes.com) for the most up-to-date technical information.

Toll Free: 800-328-4624 Phone: 913-599-0766 Fax: 913-599-0065