

Low Maintenance & Easy Installation

Bellaforté Shake polymer roofing tiles make installation easy—saving materials and cutting down on installation costs. With little to no upkeep and backed by DaVinci's lifetime warranty, DaVinci shake tiles are the perfect fit for your home for generations to come.

A Safer & More Secure Roof

Bellaforté Shake polymer cedar tiles have achieved the highest possible test ratings for fire, wind and impact giving you a more secure home for your family and has been approved and preferred by cities and subdivisions nationwide.

BELLAFORTÉ SHAKE SPECIFICATION CHART					
Shingle Dimensions					
Widths	12"	Thickness at Butt	1" average		
Length	15 1/2"–16"	Thickness at Tip	3/8"		
HIP • RIDGE • STARTER					
	One-Piece Hip & Ridge	Rake	Starter	Transition Piece	
Pieces / Bundle	10	20	20	10	
Lineal Ft / Bundle	10	20	20	10	
Pieces / Lineal Ft	1	1	1	1	
* At recommended 7" exposure					
FIELD SHINGLES PER ROOFING SQUARE					
Coursing	Roof Pitch	Max. Exposure	Bundles / Square	Shingles / Square	Weight / Square
Straight	4:12 or greater	12"	10	100	194 lbs
PACKING AND SHIPPING INFORMATION					
	# Shingles		Weight		
Per Bundle*	10		19 lbs		
Per Pallet**	720		1,368 lbs		
Per Truckload***	17,280		32,832 lbs		
* All weights are approximate ** 72 bundles per pallet *** 24 pallets per truckload					
TESTING SUMMARY					
Type of Test	Standard		Results		
Fire Test	ASTM E 108		Class A		
Impact Test	UL 2218		Class 4		
Wind Test	ASTM D 3161		Certified to 110MPH*		
Building Code Approvals: ICC-ES ESR 2119, Miami-Dade County, FL NOA No. 12-0831.01 and TDI					

* Go to www.davinciroofscapes.com for the most up-to-date technical information.

Toll Free: 800-328-4624 Phone: 913-599-0766 Fax: 913-599-0065