

# Low Maintenance & Easy Installation

Bellaforté Shake polymer roofing tiles make installation easy—saving materials and cutting down on installation costs. With little to no upkeep and backed by DaVinci's lifetime warranty, DaVinci shake tiles are the perfect fit for your home for generations to come.

## A Safer & More Secure Roof

Bellaforté Shake polymer cedar tiles have achieved the highest possible test ratings for fire, wind and impact giving you a more secure home for your family and has been approved and preferred by cities and subdivisions nationwide.

| BELLAFORTÉ SHAKE SPECIFICATION CHART   |                       |                   |                      |                   |                 |
|--|-----------------------|-------------------|----------------------|-------------------|-----------------|
| Shingle Dimensions   |                       |                   |                      |                   |                 |
| Widths   | 12"                   | Thickness at Butt | 1" average           |                   |                 |
| Length   | 15 1/2"–16"           | Thickness at Tip  | 3/8"                 |                   |                 |
| HIP • RIDGE • STARTER  |                       |                   |                      |                   |                 |
|  | One-Piece Hip & Ridge | Rake              | Starter              | Transition Piece  |                 |
| Pieces / Bundle  | 10                    | 20                | 20                   | 10                |                 |
| Lineal Ft / Bundle   | 10                    | 20                | 20                   | 10                |                 |
| Pieces / Lineal Ft   | 1                     | 1                 | 1                    | 1                 |                 |
| * At recommended 7" exposure   |                       |                   |                      |                   |                 |
| FIELD SHINGLES PER ROOFING SQUARE  |                       |                   |                      |                   |                 |
| Coursing   | Roof Pitch            | Max. Exposure     | Bundles / Square     | Shingles / Square | Weight / Square |
| Straight   | 4:12 or greater       | 12"               | 10                   | 100               | 194 lbs         |
| PACKING AND SHIPPING INFORMATION   |                       |                   |                      |                   |                 |
|  | # Shingles            |                   | Weight               |                   |                 |
| Per Bundle*  | 10                    |                   | 19 lbs               |                   |                 |
| Per Pallet**   | 720                   |                   | 1,368 lbs            |                   |                 |
| Per Truckload***   | 17,280                |                   | 32,832 lbs           |                   |                 |
| * All weights are approximate ** 72 bundles per pallet *** 24 pallets per truckload        |                       |                   |                      |                   |                 |
| TESTING SUMMARY  |                       |                   |                      |                   |                 |
| Type of Test   | Standard              |                   | Results              |                   |                 |
| Fire Test  | ASTM E 108            |                   | Class A              |                   |                 |
| Impact Test  | UL 2218               |                   | Class 4              |                   |                 |
| Wind Test  | ASTM D 3161           |                   | Certified to 110MPH* |                   |                 |
| Building Code Approvals: ICC-ES ESR 2119, Miami-Dade County, FL NOA No. 12-0831.01 and TDI |                       |                   |                      |                   |                 |

\* Go to [www.davinciroofscapes.com](http://www.davinciroofscapes.com) for the most up-to-date technical information.

Toll Free: 800-328-4624 Phone: 913-599-0766 Fax: 913-599-0065