

Low Maintenance & Easy Installation

DaVinci Fancy Shake polymer roofing tiles make installation easy—saving materials and cutting down on installation costs. With little to no upkeep and backed by DaVinci's lifetime warranty, DaVinci shake tiles are the perfect fit for your home for generations to come.

A Safer & More Secure Roof

Fancy Shake has achieved the highest possible test ratings for fire, wind and impact giving you a more secure home for your family and has been approved and preferred by cities and subdivisions nationwide.

FANCY SHAKE SPECIFICATION CHART					
Shingle Dimensions					
Widths	12", 7", 5"	Thickness at Butt	7/16"		
Length	18"	Thickness at Tip	1/8"		
HIP • RIDGE • STARTER					
	5" Hip & Ridge (standard)	4" Accessory Piece	12" Starter		
Pieces / Bundle	20	20	20		
Lineal Ft / Bundle	5.83*	5.83*	20		
Pieces / Lineal Ft	3.42*	3.42*	1		
* At recommended 7" exposure					
FIELD SHINGLES PER ROOFING SQUARE					
Coursing	Roof Pitch	Max. Exposure	Bundles / Square	Shingles / Square	Weight / Square
Straight or Staggered	Mansard/Siding	8"	7.2	216	275 lbs
Straight or Staggered	2" in 12" or greater	7"	8.2	246	314 lbs
Straight or Staggered	2" in 12" or greater	6"	9.6	288	366 lbs
Note 1: All calculations are based on using the recommended 3/8" gap between shingles.					
PACKING AND SHIPPING INFORMATION					
	# Shingles	Weight			
Per Bundle*	30	38 lbs			
Per Pallet**	1,440	1,824 lbs			
Per Truckload***	34,560	43,776 lbs			
* All weights are approximate ** 48 bundles per pallet *** 24 pallets per truckload					
TESTING SUMMARY					
Type of Test	Standard	Results			
Fire Test	ASTM E 108	Class A			
Impact Test	UL 2218	Class 4			
Wind Test	ASTM D 3161	Certified to 110MPH*			

* Go to www.davinciroofscapes.com for the most up-to-date technical information.

Toll Free: 800-328-4624 Phone: 913-599-0766 Fax: 913-599-0065