

Low Maintenance & Easy Installation

DaVinci Shake Multi-Width polymer roofing tiles make installation easy—saving materials and cutting down on installation costs. With little to no upkeep and backed by DaVinci's lifetime warranty, DaVinci shake tiles are the perfect fit for your home for generations to come.

A Safer & More Secure Roof

DaVinci Shake Multi-Width has achieved the highest possible test ratings for fire, wind and impact giving you a more secure home for your family and has been approved and preferred by cities and subdivisions nationwide.

DAVINCI SHAKE MULTI-WIDTH SPECIFICATION CHART					
Shingle Dimensions					
Widths	9", 8", 7", 6", 4"	Thickness at Butt	5/8"		
Length	22"	Thickness at Tip	1/4"		
HIP • RIDGE • STARTER					
	6" Hip & Ridge	One-piece Hip & Ridge	12" Valley Shingle	12" Starter	
Pieces / Bundle	20	10	10	20	
Lineal Ft / Bundle	8.33*	8.33*	4.3*	20	
Pieces / Lineal Ft	2.40*	2.40*	2.3*	1	
* At recommended 10" exposure					
FIELD SHINGLES PER ROOFING SQUARE					
Coursing	Roof Pitch	Max. Exposure	Bundles / Square	Shingles / Square	Weight / Square
Straight	4:12 or greater	10"	8	192	298 lbs
Staggered	4:12 or greater	9"	9	216	329 lbs
Note 1: All calculations are based on using the recommended 3/8" gap between shingles.					
Note 2: Felt interlay is suggested on any pitch and required on pitches less than 6" in 12"					
PACKING AND SHIPPING INFORMATION					
	# Shingles	Weight			
Per Bundle*	24	37 lbs			
Per Pallet**	1,200	1,776 lbs			
Per Truckload***	28,800	42,624 lbs			
* All weights are approximate ** 48 bundles per pallet *** 24 pallets per truckload					
TESTING SUMMARY					
Type of Test	Standard	Results			
Fire Test	ASTM E 108	Class A			
Impact Test	UL 2218	Class 4			
Wind Test	ASTM D 3161	Certified to 110MPH*			
Building Code Approvals: ICC-ES ESR 2119, Miami-Dade County, FL NOA No. 13-0107.01 and TDI					

* Go to www.davinciroofscapes.com for the most up-to-date technical information.

Toll Free: 800-328-4624 Phone: 913-599-0766 Fax: 913-599-0065