

DAVINCI SHAKE

MULTI-WIDTH SHAKE

Widths - 9", 8", 7", 6", 4"	Length - 22"	Thickness at Butt - 5/8"	Thickness at Tip - 1/4"
-----------------------------	--------------	--------------------------	-------------------------

FIELD SHINGLES PER ROOFING SQUARE

Coursing	Roof Pitch	Max. Exposure	Pieces / Bundle	Bundles / Square	Weight / Square	Nails Required
Straight	3:12 or greater	10"	24	8	300 lbs	384/SQ
Staggered	3:12 or greater	9"	24	9	333 lbs	432/SQ

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Felt interlay is suggested on any pitch and required on pitches less than 6" in 12"

HIP • RIDGE • STARTER • ACCESSORY

	6" Hip & Ridge	One-Piece Hip & Ridge	12" Valley Shingle	12" Starter	12" Solid Accessory Tile
Pieces / Bundle	20	10	10	20	10
Linear Ft / Bundle	8.33*	10	4.16*	20	10
Pieces / Linear Ft	2.40*	1.0**	1.2*	1	1
Nails Required	40/BDL	20/BDL	20/BDL	40/BDL	20/BDL

*At recommended 10" exposure **At recommended 12" exposure

SINGLE-WIDTH SHAKE

Widths - 9"	Length - 22"	Thickness at Butt - 5/8"	Thickness at Tip - 1/4"
-------------	--------------	--------------------------	-------------------------

FIELD SHINGLES PER ROOFING SQUARE

Coursing	Roof Pitch	Max. Exposure	Pieces / Bundle	Bundles / Square	Weight / Square	Nails Required
Straight	3:12 or greater	10"	22	7	297 lbs	308/SQ
Staggered	3:12 or greater	9"	22	7.8	330 lbs	344/SQ

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Felt interlay is suggested on any pitch and required on pitches less than 6" in 12"

HIP • RIDGE • STARTER • ACCESSORY

	6" Hip & Ridge	One-Piece Hip & Ridge	12" Valley Shingle	12" Starter	12" Solid Accessory Tile
Pieces / Bundle	20	10	10	20	10
Linear Ft / Bundle	8.33*	10	4.16*	20	10
Pieces / Linear Ft	2.40*	1.0**	1.2*	1	1
Nails Required	40/BDL	20/BDL	20/BDL	40/BDL	20/BDL

*At recommended 10" exposure **At recommended 12" exposure

BELLAFORTÉ SHAKE

Widths - 12"	Length - 15.5-16"	Thickness at Butt - 1" average	Thickness at Tip - 3/8"
--------------	-------------------	--------------------------------	-------------------------

FIELD SHINGLES PER ROOFING SQUARE

Coursing	Roof Pitch	Max. Exposure	Pieces / Bundle	Bundles / Square	Weight / Square	Nails Required
Straight	3:12 or greater	12"	10	10	194 lbs	200/SQ

HIP • RIDGE • STARTER • ACCESSORY

	One-Piece Hip & Ridge	Rake	Starter	Transition Piece	Solid Valley Piece
Pieces / Bundle	10	20	20	10	10
Linear Ft / Bundle	10	20	20	10	10
Pieces / Linear Ft	1	1	1	1	1
Nails Required	20/BDL	40/BDL	40/BDL	30/BDL	20/BDL

TESTING & BUILDING CODE APPROVALS

Class A Fire; Class 4 Impact; Certified to 110MPH
 ICC-ES ESR-2119; Miami-Dade County, FL; CA Title 24; Texas Dept. of Insurance; LEED contribution; CCMC 14094-R; WUI 4175-2772:0500

* Go to www.davinciroofscapes.com for the most up-to-date technical information.

DAVINCI SHAKE

SELECT SHAKE

Widths - 10", 8"	Length - 22"	Thickness at Butt - 5/8"	Thickness at Tip - 1/4"
------------------	--------------	--------------------------	-------------------------

FIELD SHINGLES PER ROOFING SQUARE

Coursing	Roof Pitch	Max. Exposure	Pieces / Bundle	Bundles / Square	Weight / Square	Nails Required
Straight	3:12 or greater	10"	22	7	284 lbs	308/SQ

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Felt interlay is suggested on any pitch and required on pitches less than 6" in 12"

HIP • RIDGE • STARTER • ACCESSORY

	One-Piece Hip & Ridge	12" Starter
Pieces / Bundle	10	20
Linear Ft / Bundle	10	20
Pieces / Linear Ft	1.0*	1
Nails Required	20/BDL	40/BDL

*At recommended 10" exposure

HAND-SPLIT SHAKE SIDING

Widths - 8", 10"	Length - 18"	Thickness at Butt - 5/8"	Thickness at Tip - 1/4"
------------------	--------------	--------------------------	-------------------------

FIELD SHINGLES PER ROOFING SQUARE

Coursing	Exposure	Pieces / Bundle	Bundles / Square	Weight / Square	Nails Required
Straight	8"	22	8.7	313 lbs	383/SQ
Straight	7"	22	10	360 lbs	440/SQ
Straight	6"	22	11.4	410 lbs	502/SQ

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Felt interlay is suggested on any pitch and required on pitches less than 6" in 12"

HIP • RIDGE • STARTER • ACCESSORY

	12" Starter
Pieces / Bundle	20
Linear Ft / Bundle	20
Pieces / Linear Ft	1
Nails Required	40/BDL

TESTING & BUILDING CODE APPROVALS

Class A Fire; Class 4 Impact; Certified to 110MPH
 ICC-ES ESR-2119; Miami-Dade County, FL; CA Title 24; Texas Dept. of Insurance; LEED contribution; CCMC 14094-R; WUI 4175-2772:0500

* Go to www.davinciroofscapes.com for the most up-to-date technical information.